


PRODUCT NAME	SUPER FRESH HIGH-HUMIDITY CHILLER (COMMERCIAL REFRIGERATOR)	
MODEL	UQD-060WMC-TH	
POWER SUPPLY	Single Phase 220V 50Hz	
OUTSIDE DIMENSIONS	(W) 610mm× (D) 800mm× (H) 1950mm	
INSIDE DIMENSIONS	Room A: (W) 510mm× (D) 650mm× (H) 710mm Room B: (W) 510mm× (D) 650mm× (H) 695mm	
EFFECTIVE CAPACITY	Room A: 246L, Room B: 241L	
WEIGHT	130kg	
EXTERIOR MATERIAL	Stainless Steel (Front and Sides) Galvanized Steel (Top) Galvanized Steel (Rear and Bottom)	
INTERIOR MATERIAL	Stainless Steel	
DOOR MATERIAL	Stainless Steel (Front) ABS Resin, Magnet-Style Packing (Rear)	
INSULATION MATERIAL	Polyurethane Foam	
ADJUSTABLE SHELF MATERIAL	Steel Wire Resin coating	
COOLING PERFORMANCE	-5°C to 15°C (No Load and Ambient Temperature of 30°C)	
INTERNAL HUMIDITY	90% or higher (Internal Temperature of 1°C)	
COMPRESSOR	425W	
REFRIGERANT CONTROL METHOD	Expansion Valve	
CONDENSER	Fin and Tube Type, Forced Air-Cooling	
EVAPORATOR	Wall Surface Cooling, Natural Convection Type	
REFRIGERANT	R-404A	
TEMPERATURE CONTROL	Microcomputer Control, Digital Display	
DEFROST CONTROL	Manual Start, Off-Cycle Defrost	
APPLICABLE BREAKER CAPACITY	Single Phase 220V 15A 50Hz	
POWER CORD	2.0m (Plug with Earth Wire)	
VOLTAGE RANGE	220V±6%	
COOLING	Operation Current	2.3A
	Starting Current	11A
	Power Consumption	470W
	Power Factor	92%
DEFROSTING	Operation Current	—
	Power Consumption	—
OPERATING TEMPERATURE RANGE	5°C to 35°C	
RADIATION OF HEAT CAPACITY	705W	
ADJUSTABLE LEG	Resin made Leg form 95 to 130mm	
ACCESSORIES	Shelves (4 Pieces) Drain Accessory (1 Set)	
OTHER ACCESSORIES	Condenser Filter	

We may change it without a notice for improvement about the specifications and design.

- ☐ SUCTION AIR
- ▣ EXHAUST AIR

PLUG TYPE



		REFERENCE NO
DATA 08 . 06 . 2020	SCALE 1/20	DRAWING NO
GALILEI (THAILAND) CO., LTD.		